



4-channel counter

μCAN.4.ci-BOX

4-channel up/down counter up to 500 kHz


The μCAN.4.ci-BOX is equipped with 4 fast up/down counters of up to 500 kHz. The CAN unit acquires binary impulses which are processed and sent on to a superordinate system via galvanically isolated connections. In addition, input signal frequencies may be set according to specific requirements.

4 outputs are switched according to the respective counter status and can be utilized as high-speed control signals. Outlets may be loaded up to 1.4 A and are short circuit protected.



Features

- 4 up / down counters
- Frequency measurement
- 4 I/O terminals freely configurable
- Outlets to be loaded up to 1.4 A
- Protocol: CANopen CiA 404
- LEDs for device and signal status indication
- 3-conductor plugs
- output voltage from 5 .. 50 V



Lindlaustraße 2c
53842 Troisdorf
Germany

Tel +49 - 2241 - 25 65 9 - 0
Fax +49 - 2241 - 25 65 9 - 11

info@microcontrol.net
www.microcontrol.net

Technical Data	4-channel counter μCAN.4.ci-BOX
Number of channels	4 high-speed counters, 4 I/O terminlas freely configurable
Power supply voltage	8...60 V DC, polarity protected
Power consumption	1.5W (60mA @ 24V DC) without load
Electrical isolation	Field bus / control voltage: 500V _{eff}
Operating temperature	-40°C...+85°C (others upon request)
Transfer rate	20kBit/sec to 1MBit/sec
Protocol	CANopen Cia404 (CAN 2.0A and 2.0B)
Number of PDOs	2 transmit PDOs
Configuration	Selection of input / output mode via field bus Baud rate and module address via DIP-switches
Status display	2 bi-color LEDs for module status information 8 bi-color LEDs for input / output status
Outputs	No galvanic isolation of outputs, long-term short circuit protection, maximum output current per output 1.4 A (total current over all outputs up to 6A) Short circuit and overload detection / 5 – 50V DC
Inputs	No galvanic isolation of inputs Input voltage range "high" dynamic at 55% of driver input voltage
Measurement frequency	500 kHz
Protection class	IP66
Housing	Die cast aluminum 125x80x57mm (LxWxH)
EMC	EN 50082-compliant

Order Number	Description
12.88.008	μ CAN.4.ci-BOX 4-channel counter with CANopen, configured for metric cable gland. Connection via screw terminals.
90.01.114	metric cable gland set for 4-channel field modules